

# ECOLUM

## LED



Lasts up to **8 years**\*\*

**85%**  
ENERGY SAVINGS\*






















### JUNE 2017 PRICE LIST

(Prices are subject to change without prior notice)

\*Energy savings compared to standard incandescent lamp.  
\*\*Computed at 2.7 hours per day when used in the right conditions.

## ECOLUM LED













### LED LAMPS

LED LAMPS	Wattage	Lumen Output	Color Temperature	Dimmable	Lamp Base	Dimensions	PKG.	Suggested Retail Price
Product Description	W	Lm	K	Yes/No		(a x b x c mm)	Pcs./Ctn.	SRP
			 8,000 H		110-240V Wide Voltage	 200° Beam Angle	 80 CRI	
<b>New!</b> CBI203DL	3	250	6500 • Daylight	no	E27	45 x 85	40	<b>65</b>
CBI205DL	5	450	6500 • Daylight	no	E27	55 x 100	40	<b>75</b>
CBI207DL	7	600	6500 • Daylight	no	E27	55 x 100	40	<b>90</b>
CBI209DL	9	800	6500 • Daylight	no	E27	60 x 115	40	<b>100</b>
CBI211DL	11	1050	6500 • Daylight	no	E27	60 x 115	40	<b>120</b>
CBI213DL	13	1500	6500 • Daylight	no	E27	70 x 135	40	<b>170</b>
<i>*Replacement for CBI3 series</i>								
			 10,000 H		100-240V Wide Voltage	 220° Beam Angle		
CFS01T8DL09	9	750	6500 • Daylight	no	G13	25.4 x 600	20	<b>150</b>
CFS01T8DL18	18	1500	6500 • Daylight	no	G13	25.4 x 1200	20	<b>190</b>
			 10,000 H		100-240V Wide Voltage	 220° Beam Angle		
CBT511/DL09	9	750	6500 • Daylight	no	G13	43 x 610 x 31	20	<b>200</b>
CBT511/DL18	18	1500	6500 • Daylight	no	G13	43 x 1220 x 31	10	<b>250</b>
			 10,000 H		220V Operating Voltage	 200° Beam Angle		
ECBTS11/DL07	7	600	6500 • Daylight	no	G13	43 x 610 x 31	20	<b>195</b>
ECBTS11/DL16	16	1400	6500 • Daylight	no	G13	43 x 1220 x 31	20	<b>245</b>
			 10,000 H		100-240V Wide Voltage	 135° Beam Angle	 80 CRI	
<b>New!</b> CBTST5DL05	5	400	6500 • Daylight	no	N/A	34 x 315 x 22	25	<b>150</b>
CBTST5WW05	5	400	3000 • Warm White	no	N/A	34 x 315 x 22	25	<b>150</b>
CBTST5DL08	8	640	6500 • Daylight	no	N/A	34 x 575 x 22	25	<b>190</b>
CBTST5WW08	8	640	3000 • Warm White	no	N/A	34 x 575 x 22	25	<b>190</b>
CBTST5DL16	16	1260	6500 • Daylight	no	N/A	34 x 1175 x 22	25	<b>265</b>
CBTST5WW16	16	1260	3000 • Warm White	no	N/A	34 x 1175 x 22	25	<b>265</b>
			 20,000 H		100-240V Wide Voltage	 120° Beam Angle	 IP65 IP Rating	
<b>New!</b> CFL1010DL	10	700	6500 • Daylight	no	N/A	159 x 129 x 43	12	<b>410</b>
CFL1020DL	20	1400	6500 • Daylight	no	N/A	178 x 164 x 43	12	<b>730</b>
CFL1030DL	30	2100	6500 • Daylight	no	N/A	203 x 184 x 50	12	<b>1,000</b>
CFL1050DL	50	3500	6500 • Daylight	no	N/A	242 x 180 x 53	12	<b>1,290</b>
CFL1070DL	70	4900	6500 • Daylight	no	N/A	272 x 210 x 55	12	<b>2,070</b>








LED DOWNLIGHTS	Wattage	Lumen Output	Color Temperature	Dimmable	Dimensions	Cut-out Size	PKG.	Suggested Retail Price
Product Description	W	Lm	K	Yes/No	(a x b x c mm)	mm	Pcs./Ctn.	SRP
LED Recessed Slim Downlight								
<b>New!</b>					10,000 H	110-240V Wide Voltage	120° Beam Angle	
CDL1106DL	6	450	6000 • Daylight	no	120 x 120 x 9.8	112 x 112	20	<b>220</b>
CDL1112DL	12	1000	6000 • Daylight	no	170 x 170 x 9.8	162 x 162	20	<b>350</b>
CDL1118DL	18	1500	6000 • Daylight	no	225 x 225 x 9.9	213 x 213	20	<b>480</b>
LED Recessed Slim Downlight								
<b>New!</b>					10,000 H	110-240V Wide Voltage	120° Beam Angle	
CDL2106DL	6	450	6000 • Daylight	no	Ø 120 x 9.8	Ø 112	20	<b>220</b>
CDL2112DL	12	1000	6000 • Daylight	no	Ø 170 x 9.8	Ø 162	20	<b>350</b>
CDL2118DL	18	1500	6000 • Daylight	no	Ø 225 X 9.9	Ø 213	20	<b>480</b>
LED Surface Downlight								
<b>New!</b>					10,000 H	110-240V Wide Voltage	120° Beam Angle	
CDL1206DL	6	450	6000 • Daylight	no	120 x 120 x 36	N/A	20	<b>300</b>
CDL1212DL	12	1000	6000 • Daylight	no	170 x 170 x 36	N/A	20	<b>420</b>
CDL1218DL	18	1500	6000 • Daylight	no	225 x 225 x 39	N/A	20	<b>650</b>
LED Surface Downlight								
<b>New!</b>					10,000 H	110-240V Wide Voltage	120° Beam Angle	
CDL2206DL	6	450	6000 • Daylight	no	Ø 120 x 36	N/A	20	<b>300</b>
CDL2212DL	12	1000	6000 • Daylight	no	Ø 170 x 36	N/A	20	<b>420</b>
CDL2218DL	18	1500	6000 • Daylight	no	Ø 225 x 39	N/A	20	<b>650</b>

## INDOOR FIXTURES

OPEN TYPE	Wattage	Dimensions	Packaging	Suggested Retail Price	
Product Description	W	(a x b x c mm)	Pcs./Ctn.	SRP	
Open Type Fixture Rotary Type					
			220V Operating Voltage		
ESO1/10	T8	1 x 10W	350 x 48 x 90	25	<b>150.00</b>
ESO1/20	T8	1 x 20W	610 x 48 x 90	25	<b>175.00</b>
ESO1/40	T8	1 x 40W	1220 x 48 x 90	25	<b>185.00</b>
<i>Fixture with Ballast &amp; Starter</i>					
BOX TYPE					
Box Type Fluorescent Fixture for Straight FL Tube					
			220V Operating Voltage		
EXB20	T8	1 x 20W	640 x 54 x 80	16	<b>195.00</b>
EXB40	T8	1 x 40W	1250 x 54 x 80	16	<b>245.00</b>
<i>Fixture with Ballast &amp; Starter</i>					
ELSFBT2X20/0	T8	2 x 20W	640 x 100 x 80	10	<b>225.00</b>
ELSFBT2X40/0	T8	2 x 40W	1250 x 100 x 80	10	<b>275.00</b>
<i>Fixture Only</i>					
LOUVERS					
Industrial Type with Aluminum Reflector					
			220V Operating Voltage		
ESLIA2x20/1	T8	2 x 20W	640 x 190 x 80	2	<b>690.00</b>
<i>Fixture with Ballast &amp; Starter</i>					

LOUVERS		Wattage	Dimensions	Packaging	Suggested Retail Price	
Product Description		W	(a x b x c mm)	Pcs./Ctn.	SRP	
 	<b>Industrial Type with Aluminum Reflector</b>					
	ESLIA1x20/0	T8	1 x 20W	640 x 135 x 80		<b>210.00</b>
	ESLIA1x40/0	T8	1 x 40W	1250 x 135 x 80		<b>300.00</b>
	ESLIA2x20/0	T8	2 x 20W	640 x 190 x 80		<b>300.00</b>
	ESLIA2x40/0	T8	2 x 40W	1250 x 190 x 80		<b>400.00</b>
	<i>Fixture Only</i>					
	<b>Industrial Type with Powder Coated Reflector</b>					
	ESLI1X20/0	T8	1 x 20W	640 x 135 x 80	12	<b>175.00</b>
	ESLI1X40/0	T8	1 x 40W	1250 x 135 x 80	12	<b>240.00</b>
	ESLI2X20/0	T8	2 x 20W	640 x 190 x 80	7	<b>260.00</b>
ESLI2X40/0	T8	2 x 40W	1250 x 190 x 80	7	<b>340.00</b>	
<i>Fixture Only</i>						
 	<b>220V Operating Voltage</b>					
	<b>Prismatic Type Magnetic for Straight FL Tube</b>					
	ELSSPL1X40/0	T8	1 x 40W	1260 x 90 x 80	6	<b>540.00</b>
	ELSSPL2X40/0	T8	2 x 40W	1237 x 177 x 65	4	<b>620.00</b>
<i>Fixture Only</i>						
 	<b>Recessed Type Dust Proof Louver</b>					
	ELSRDP1X20/0	T8	1 x 20W	600 x 300 x 80	2	<b>700.00</b>
	ELSRDP1X40/0	T8	1 x 40W	1200 x 300 x 80	2	<b>750.00</b>
	ELSRDP2X20/0	T8	2 x 20W	600 x 300 x 80	2	<b>750.00</b>
	ELSRDP2X40/0	T8	2 x 40W	1200 x 300 x 80	2	<b>850.00</b>
<i>Fixture Only</i>						
 	<b>Surface Type Dust Proof Louver</b>					
	ELSSDP1X20/0	T8	1 x 20W	610 x 190 x 80	2	<b>700.00</b>
	ELSSDP1X40/0	T8	1 x 40W	1220 x 190 x 80	2	<b>750.00</b>
	ELSSDP2X20/0	T8	2 x 20W	610 x 310 x 80	2	<b>750.00</b>
	ELSSDP2X40/0	T8	2 x 40W	1220 x 310 x 80	2	<b>850.00</b>
<i>Fixture Only</i>						
 	<b>Recessed Type with Aluminum Reflector</b>					
	ESLR1X20/0	T8	1 x 20W	600 x 190 x 80	2	<b>620.00</b>
	ESLR1X40/0	T8	1 x 40W	1200 x 190 x 80	2	<b>720.00</b>
	ESLR2X20/0	T8	2 x 20W	600 x 300 x 80	2	<b>630.00</b>
	ESLR2X40/0	T8	2 x 40W	1200 x 300 x 80	2	<b>790.00</b>
	ESLR3X20/0	T8	3 x 20W	600 x 600 x 80	2	<b>930.00</b>
	ESLR3X40/0	T8	3 x 40W	1200 x 600 x 80	2	<b>1,590.00</b>
	<i>Fixture Only</i>					
	<b>Wide Recessed Type with Aluminum Reflector</b>					
	ESLRW1X20/0	T8	1 x 20W	600 x 300 x 80	2	<b>670.00</b>
	ESLRW1X40/0	T8	1 x 40W	1200 x 300 x 80	2	<b>820.00</b>
ESLRW2X20/0	T8	2 x 20W	600 x 600 x 80	2	<b>780.00</b>	
ESLRW2X40/0	T8	2 x 40W	1200 x 600 x 80	2	<b>1,290.00</b>	
<i>Fixture Only</i>						
 	<b>Surface Type with Aluminum Reflector</b>					
	ESLS1X40/0	T8	1 x 40W	1220 x 190 x 80	2	<b>720.00</b>
	ESLS2X20/0	T8	2 x 20W	610 x 310 x 80	2	<b>630.00</b>
	ESLS2X40/0	T8	2 x 40W	1220 x 310 x 80	2	<b>790.00</b>
	ESLS3X20/0	T8	3 x 20W	610 x 610 x 80	2	<b>930.00</b>
	<i>Fixture Only</i>					
	<b>Wide Surface Type with Aluminum Reflector</b>					
ESLSW1X20/0	T8	1 x 20W	610 x 310 x 80	2	<b>670.00</b>	
ESLSW1X40/0	T8	1 x 40W	1220 x 310 x 80	2	<b>820.00</b>	
<i>Fixture Only</i>						

HAND-HELD FLASHLIGHTS			PKG.	Suggested Retail Price	HAND-HELD FLASHLIGHTS			PKG.	Suggested Retail Price
Product Description			Pcs./Ctn.	SRP	Product Description			Pcs./Ctn.	SRP
	Handy Torch Light					Handy Torch Light			
	EEL541R (Red)	20	95.00	EEL542		60	170.00		
	• 230V 50/60Hz			• 230V 50/60Hz					
	• Hi-Power LED			• 3 Watts Hi-Power LED					
	• 4V 400mAh Sealed Lead Acid			• 4V 900mAh Sealed Lead Acid					
• Charging Time: 12 - 15 Hrs.			• Charging Time: 12 - 15 Hrs.						
• Duration Time: 10 Hrs. = Low Torch 2.5 Hrs. = High Torch			• Duration Time: 4 Hrs. = Low Torch 1 Hr. = High Torch						
	Handy Torch Light					7 LED Mega Torch Lamp			
	EEL541G (Green)	20	95.00	EEL543		56/1	195.00		
	• 230V 50/60Hz			• 220 - 240V AC 50/60Hz					
	• Hi-Power LED			• 7 x 1500mcd 110° LED					
	• 4V 400mAh Sealed Lead Acid			• 4V 400mAh Sealed Lead Acid					
• Charging Time: 12 - 15 Hrs.			• Charging Time: 12 - 15 Hrs.						
• Duration Time: 10 Hrs. = Low Torch 2.5 Hrs. = High Torch			• Duration Time: 3 Hrs. = Torch						
	Handy Torch Light					9 LED Mega Torch Lamp			
	EEL541B (Blue)	20	95.00	EEL544		48/1	250.00		
	• 230V 50/60Hz			• 220 - 240V AC 50/60Hz					
	• Hi-Power LED			• 9 x 1500mcd 110° LED					
	• 4V 400mAh Sealed Lead Acid			• 4V 1Ah Sealed Lead Acid					
• Charging Time: 12 - 15 Hrs.			• Charging Time: 12 - 15 Hrs.						
• Duration Time: 10 Hrs. = Low Torch 2.5 Hrs. = High Torch			• Duration Time: 5 Hrs. = Torch						
	Handy Torch Light					12 LED Mega Torch Lamp			
	EEL541Y (Yellow)	20	95.00	EEL545		40/1	275.00		
	• 230V 50/60Hz			• 220 - 240V AC 50/60Hz					
	• Hi-Power LED			• 12 x 1500mcd 110° LED					
	• 4V 400mAh Sealed Lead Acid			• 4V 1Ah Sealed Lead Acid					
• Charging Time: 12 - 15 Hrs.			• Charging Time: 12 - 15 Hrs.						
• Duration Time: 10 Hrs. = Low Torch 2.5 Hrs. = High Torch			• Duration Time: 4 Hrs. = Torch						

EXIT LIGHTS	Lamp	Charging Time	Usage Duration	Color	PKG.	Suggested Retail Price	
Product Description		Hours	Minutes		Pcs./Ctn.	SRP	
	4 LED Exit Light Milled Aluminum Type Double-sided Face 1.2V, 600mAh Rechargeable Ni-Cd Battery		220V AC Operating Voltage				
	 EEL211	4 x 1500mcd 110° LED	24 Hrs.	90 Minutes	• Green	20	650.00
	 EEL212	4 x 1500mcd 110° LED	24 Hrs.	90 Minutes	• Green	20	650.00
	 EEL213	4 x 1500mcd 110° LED	24 Hrs.	90 Minutes	• Green	20	650.00
	 EEL214	4 x 1500mcd 110° LED	24 Hrs.	90 Minutes	• Green	20	650.00
	 EEL215	4 x 1500mcd 110° LED	24 Hrs.	90 Minutes	• Green	20	650.00
	 EEL216	4 x 1500mcd 110° LED	24 Hrs.	90 Minutes	• Green	20	650.00

**FIREFLY ELECTRIC & LIGHTING CORP.**

7/F Zen Offices Bldg. 1111 Natividad Lopez St., Ermita, Manila, Philippines  
 T: (02) 7891000 (Trunkline)  
 www.fireflyelectric.com • info@fireflyelectric.com

Contact Person: